


EcoLam^R





	Recyclable mono-PE laminate with extra heat resistance
 General properties 	 Monomaterial In line with Recyclass [™] Design for Recycling Guidelines* Compatible with readily available sorting & recycling technologies commonly used at industrial scale in the recycling sector in Europe for the LDPE-fraction Ideal for replacement of non-recyclable multipolymer structures Barrier to water vapor High optical clarity Available Transparent / White and Gloss / Matt Printable by Rotogravure and Flexo Heat sealable: Fin or Lap seal & Lock or Peel seal Easy tear properties possible *Subject to final packaging design and filling good
Structure	oPE / PE
 Barrier properties 	WVTR (38 ºC, 90% RH) < 6 [g/(m²⋅day)] OTR (23 ºC, 75% RH) - [cm³/(m²⋅day⋅bar)]
 Certificates 	Recyclass Letter of Compatibility "Design for Recycling"
 Applications 	VFFS and HFFSPremade bags
 Products 	 Cereals, Pasta, Rice, Sugar Confectionery Beverages Hygiene and Home Care Products

Constantia Flexibles Group GmbH Rivergate, Handelskai 92, 1200 Wien T +43 1 888 5640-1000, F +43 1 888 5640-91000 office@cflex.com www.cflex.com