


- This data sheet describes Tri-Foil® WP F-217® HY products
- A clear PET film bonded to a white LDPE film bonded to aluminum foil bonded to three-ply co-extruded F-217® HY liner



Typical Product Attributes

Construction

Structure F-217® HY / AL foil / White LDPE / Polyester	F-217® HY / 8,9µm / 50,8µm / 12,7µm	F-217® HY / 0.00035" / 0.002" / 0.0005"
Color	White or as Specified	White or as Specified
Density		
for 20 ~ 30 mil (0,51 ~ 0,76 mm) of F-217® HY	0,50 ± 0,03 g / cm ³	31 ± 2 lbs / ft ³
for 35 ~ 125 mil (0,89 ~ 3,18 mm) of F-217® HY	0,43 ± 0,03 g / cm ³	27 ± 2 lbs / ft ³
Thickness Tolerance		
for 20 ~ 60 mil (0,51 ~ 1,52 mm) of F-217® HY	± 0,127 mm	± 5 mil
for 65 ~ 90 mil (1,65 ~ 2,29 mm) of F-217® HY	± 0,178 mm	± 7 mil
for 95 ~ 125 mil (2,41 ~ 3,18 mm) of F-217® HY	± 0,254 mm	± 10 mil
Available Width		
for 20 ~ 60 mil (0,51 ~ 1,52 mm) of F-217® HY	25,4 ~ 482,6 mm	1 ~ 19 inch
for 65 ~ 125 mil (1,65 ~ 3,18 mm) of F-217® HY	25,4 ~ 228,6 mm	1 ~ 9 inch
Width tolerance	± 1,6 mm	± 1/16 inch

Regulatory Compliance

FDA Compliance	21 CFR 177.1520 (Olefin Polymers) 21 CFR 177.1210 (Closures with Sealing Gaskets for Food Containers) 21 CFR 175.300 (Resinous and Polymeric Coatings)
Drug Master File (DMF)	2434
Other Compliances	USFDA Food Allergen Guidelines; California Proposition 65 labeling requirements; Limitations of heavy metals in packaging per CONEG & EU 94/62/EC, article 11

Original Date: 11/20/2012
Revised Date: N/A
Revision Number: 0
Created by SR

DISCLAIMER: This information is believed to be accurate at the time of printing and is subject to change without notice. Providing this information does not convey any licenses under any patent rights or other intellectual property rights of TRI-SEAL or others. **TRI-SEAL MAKES NO WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO THIS INFORMATION AND DISCLAIMS ALL LIABILITY FROM RELIANCE ON IT.** TRI-SEAL's only warranties for this product are those written warranties as may be agreed to by TRI-SEAL and its customers. **TRI-SEAL SPECIFICALLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE PRODUCT, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE.**

Tri-Seal
900 Bradley Hill Road
Blauvelt, NY 10913
Tel: (845) 353-3300 – Fax: (845) 353-3376
<http://www.tri-seal.com>