

## Features

- High performance peelable lidding for all tray types
- Solvent free coating process for reduced environmental impact
- Anti-fog properties
- Suitable for printing and lamination
- Available with 30% PCR content PET

PROPERTY	UNITS	METHODS	TYPICAL VALUES			
BASE FILM THICKNESS	µm	ASTM F2251	18	23	36	50
TOTAL THICKNESS	µm	ASTM F2251	26	31	44	58
UNIT WEIGHT	g/m <sup>2</sup>	ASTM F2217	33.4	40.4	58.6	78.2
YIELD	m <sup>2</sup> /kg	ASTM D4321	29.94	24.75	17.06	12.78
HEAT SEALING RANGE	°C	ASTM F2029	140 - 220	140 - 220	140 - 220	140 - 220
MAX TEMPERATURE AT SEALING TOOLS	°C	ASTM F2029	225	225	225	225
PEAK SEAL STRENGTH	g/15mm	ASTM F88	750 - 850	750 - 850	750 - 850	750 - 800
HAZE	%	ASTM D 1003	7	7	7	8
OTR	cm <sup>3</sup> /(m <sup>2</sup> .day)	ASTM D 3985	80	65	50	50
WVTR	g/(m <sup>2</sup> .day)	ASTM F 1249	22	16	12	12

## Seals to

- APET
- rPET
- APET lined paperboard
- CPET
- PP
- PE
- PVC
- ALU
- PS

## Regulatory and Storage Information

Complies with EC No 1935/2004 and EU No 10/2011 Regulations. Please note that it is the responsibility of the user to test the suitability of our product for the intended application in combination with the actual food stuff.

Product must be stored at ambient temperature (15-25°C recommended), 40-60% relative humidity, out of direct sunlight or heat sources. It should be allowed to reach operating room temperature before use.

## Suitable for

- Frozen
- Chilled
- Microwave
- Oven
- All types of foods

For more information please visit [www.sappi.com](http://www.sappi.com)

This document is for information purposes only. The information given has been prepared to the best of our knowledge i.e. based on due diligence and the state of research at the time of its release date. It does not provide any warranty or guarantee for specific properties or for suitability for a specific purpose or application. The responsibility for testing the suitability of the product for specific applications lies entirely with the purchaser. We reserve our right to change this document at any time.